



**GENERAL & TECHNICAL SPECIFICATIONS**



**WEB WIDTH**  
Max: 1200mm



**PRINT SPEED**  
300 or 150 mm / sec.



**RESOLUTION**  
HQ: 1600x1600 dpi's



**CMYK**  
2 liter ink tanks

<b>DIMENSIONS</b>	width 2352 mm / depth 2280 mm / height 1610 mm & Weight: 1000Kg
<b>POWER CONSUMPTION</b>	3,5kW - 230V AC - 15A - 50Hz
<b>OPERATION ENVIRONMENT</b>	<b>Operation:</b> 20°C/68°F to 30°C/86°F (25°C/77°F Recommended); <b>Humidity:</b> 22 to 80% RH (non-condensing)
<b>PLATFORM</b>	<ul style="list-style-type: none"> <li>Embedded controller &amp; QA chips</li> <li>Ink Delivery System with intermediary reservoirs</li> <li>Modular, multi-functional maintenance stations</li> <li>Large service door &amp; Easy ink tank access</li> </ul>
<b>INTERFACE</b>	Unique and user-friendly software
<b>RIP SOFTWARE (OPTIONAL)</b>	CALDERA



Powered by **memjet**

**Custom corrugated  
Carton boxes &  
Display**

The **NS MULTI**  
on Detail

A flat-bed digital corrugated printer for professional custom packaging.

